

Description

The invention involves a mixing and reducing machine with an upward-conveying mixing spiral that rotates around a vertical rotational axle.

5

A machine of this type with two interlocking flat helical springs is known, for example, from the patent DE-23-34 789 A1 or the patent DE 26 38 112 A1. In these previously known mixing and reducing machines, two spirals that mesh with each other are provided. They are mounted on rotating axles that are set apart from each other at a distance to the side. For these rotating axles, between two and four rotary transmission leadthroughs must be provided, depending on the construction, through the cover or the bottom of the container in which the spirals are provided. This container also has an expensive double construction with an essentially 8-shaped cross-section. This structural form does indeed make possible an intensive mixing, in which relatively small portions of the mixed good are stirred by the one and then by the other spiral, but is very complicated in its design.

15

The purpose of the invention presented here is thus to provide a corresponding mixing and reducing machine in which a simpler construction is possible, in which, in particular, the container construction is less complicated, and with which, however, in spite of that, a sufficient mixing quality is achieved.

20

This purpose is achieved according to the invention in that after the first mixing spiral mentioned, a second mixing spiral is arranged in the axial direction, whereby a transition zone extends between the mixing spirals in the axial direction.

25

The invention has the advantage that only one rotating axle must be present. This axle can be set in bearings in a correspondingly simple manner with only one or at maximum two rotating embodiments on the container provided. Moreover, the invention has the advantage that although only one rotating axle is present in it, a sufficient intermixing is achieved. This is especially possible in a simple container in the form of a cylinder that can be manufactured in an uncomplicated manner.

30

In the previously known mixing machines with only one rotating axle, only one mixing spiral is customarily present, and it is continuous. This makes it so that the mixed good is conveyed continuously upwards in the area of the mixing spiral that is radially to the outside relative to the rotating axle, and then – customarily in the area of the centrally arranged rotating axle – drops to the bottom again because of the force of gravity. This does not lead, in the end, to a fast and intensive mixing.

35

In the embodiment form now proposed according to the invention with two mixing spirals that are connected one after the other in the axial direction and are separated by a transition zone, it is achieved on the other hand that zones having different axial conveying quantities are connected one after the other, which promotes the intensive intermixing. This is especially the case when the transition zone is free of mixing spirals and the mixed good is thus slowed down at the beginning of the transition zone and is

40

45

D9858137, 05.15.01

accelerated again at the end of the transition zone through the subsequently connected second mixing spiral. The shearing forces acting as a result in the mixed good lead to a surprisingly intensive mixing.

- 5 It should also be mentioned here that for larger systems, several mixing spirals arranged axially behind each other can also be present, each separated by transition zones. For the sake of simplicity, this will not be dealt with separately in the following.

- 10 Fundamentally, the two mixing spirals connected axially one after the other, both of which fundamentally convey in the same axial direction upwards, also have different axial conveyed quantities, whereby in the axial direction, an additional shearing gradient occurs, which amplifies the intermixing.

- 15 This different axial conveyed quantity can either be achieved in that the two mixing spirals have different helix angles or, however, in that the two mixing spirals have different spiral blade widths.

It is also possible to connect single-flighted or multiple-flighted spirals after each other.

- 20 As an additional possibility, to increase the shearing effect in the area of the transition zone, in order to thus increase the mixing effect, it can be provided that the two mixing spirals that are connected one after the other have different rotational speeds or also, however, have different rotational directions.
- 25 In order to increase the effectiveness of mixing with the spirals, it has proven to be especially favorable if at least one of the spirals provided is interrupted in the circumferential direction and is comprised of mixing blades that are connected after each other in the circumferential direction. Through this type of interruption of the mixing spiral, the mixed good is mixed in an especially intensive manner, since it is moved in
- 30 especially small volumes by the blades, and comes to rest again. Moreover, each mixing blade can be equipped with a different conveying angle both in the axial and in the radial direction, whereby an additionally improved mixing effect can be obtained.

- 35 A further improvement of the intermixing is achieved when at least individual mixing blades have, on their ends that are trailing in the rotating direction, a lifting edge that is bent upwards, through which a brief impulse directed upwards is imparted to a mixed good portion lifted by the mixing blades, before this mixed good portion begins to drop again due to the force of gravity, whereby it is then picked up again by a trailing mixing blade and further intermixed accordingly.

- 40 In a special embodiment form of this type of mixing spiral comprised of mixing blades, two mixing blades at a time are arranged essentially above each other are connected to each other by an essentially vertically running blade carrier that is set in the rotational direction. With this blade carrier, on which if necessary, even more than two blades
- 45 arranged above each other can be mounted, the mixed good can be accelerated or slowed down in the radial direction.

This is possibly further amplified in that the mixing blades (and/or the blade carrier that connects them) are attached through carrier arms to a central shaft, the front surface of which is chamfered increasingly, at least in sections, radially to the outside. This also increases a mixing effect in the radial direction of the otherwise only vertically operating mixer.

In order to further intensify the mixing effect, at least individual mixing blades can additionally mesh on their outer side with catchment elements located on the container wall. Through the shearing that occurs in the area of the catchment elements, the mixing effect is greatly increased.

In the process, the catchment elements can involve both closed ring elements as well as toothed ring elements that are mounted on the container wall. These ring elements can in the process either be arranged only in segments over the circumference of the circumference of the container or, instead over its entire circumference.

An additional improvement of the mixing effect is obtained when on one end of the mixing blades a shearing head is arranged essentially aligned with the vertical rotating axle, with which the mixed good that is dropping centrally around the rotating axle is again sheared. Also, a desired radial or axial conveyance of the mixed good can be influenced here. Advantageously, this shearing head acts together with a counter head, which has a different rotational speed and/or direction.

Additional advantages and characteristics of the invention result from the following description of an embodiment example. Shown are:

- Figure 1 a section view of a mixing and reducing machine according to the invention;
- Figure 2 a view of a reducing machine that mixes according to the invention;
- Figure 3 a schematic diagram showing the arrangement of mixing spirals that are comprised of mixing blades;
- Figure 4 a section view of a special embodiment form of a mixing and reducing machine;
- Figure 5 a view of a mixing and reducing machine according to Figure 4.

Figure 1 shows a mixing and reducing machine according to the invention in the cut side view.

A drum-shaped housing 1 is shown which has a cylindrical shape and is closed by a cover 2 that is screwed on and a welded-on bottom 3.

In the cover 2, a feed opening 4 is located. In the bottom 3, an outlet opening 5 for the material to be mixed is located.

Furthermore, in the example depicted here, an additional supply lance 6 is depicted, by which liquid that is yet to be mixed in during the mixing operation can be possibly added to the mixed good that is filled through the supply opening 4.

- 5 In the cover 2, a shaft 8 is conducted into the housing 1 on a shaft leadthrough 7, the vertical rotating axle 9 of which coincides with the middle axle of the housing 1.

On this shaft 8, two mixing spirals that convey upwards are mounted above each other. With them, the mixed good is revolved in the vertical mixer as indicated by the dot-dash
 10 lines 10: on the circumferential area of the housing 1, the mixed good is conveyed upwards through the two mixing spirals and drops down again in the vicinity of the shaft 8, in particular, also because of the force of gravity.

The mixing spirals are, as can be recognized in the view in Figure 2, not continuous, but
 15 instead they are interrupted in the circumferential direction and are comprised of several mixing blades 11 to 13 that are connected one after the other in the circumferential direction. Figure 3 shows schematically how the individual mixing blades are arranged. In Figure 2, a zero-line is marked for this purpose, starting from which an angle α is measured. The first mixing blade 11.1 is arranged at an angle of $\alpha = 0^\circ$, after which the
 20 mixing blade 12.1 is arranged at an angle of $\alpha = 120^\circ$, which is in turn followed by the mixing blade 13.1 at an angle of $\alpha = 240^\circ$. A small portion of the mixed good is grasped by the first mixing blade and correspondingly conveyed axially and radially and again released. Each subsequent mixing blade picks up parts of this conveyed portion and conveys and mixes it further.

Each of the aforementioned mixing blades is connected via a blade carrier 17, as is recognized in Figure 1, to an additional mixing blade sitting above and slightly offset in the circumferential direction. These blades are thus, as is recognized in Figure 3,
 25 arranged as mixing blades 11.2, 12.2 or 13.2 correspondingly on the circumferential positions at angles α of 0° , 120° , 240° .

Each of these mixing blades has on its end that is trailing in the rotational direction, a lifting edge 18 that is angled upwards. Through it, a portion of the mixed good, which was lifted by the mixing blade, is given a slight impulse upwards, before it drops again
 35 slightly because of the force of gravity, and is picked up by the following mixing blade and conducted again further upwards.

It is now essential to the invention that the mixing blade 13.2 shown is not directly followed by another mixing blade (in the example shown here, 14.1), but instead that here
 40 a transition zone 19 extends in the axial direction, which is free of a mixing spiral in the example shown here. – In other words, in this area, the mixed good that was conveyed until now is again brought to rest, before it is picked up by the following other mixing blades 14.1, 15.1 and 16.1 and/or then 14.2, 15.2 and 16.2, which are positioned at circumferential angles of $\alpha = 60^\circ$, 180° , or 300° .

45

5

10

15

20

25

35

40

45

in Figure 5 in the lower half, the catchment elements can also be constructed as toothed rings 26, which especially further increases the shearing action.

In Figure 4, it is furthermore recognized that the shaft 8 is set in bearings so that it overhangs above the cover 2, so that the mixing station shaft ends at a greater distance above the container bottom 3. On this lower end of the shaft 8, a shearing head 27 is arranged, which rotates together with the shaft 8. In the process, it is in mesh with a counter-shearing head, which is driven through its own drive shaft 29 in the opposite direction, whereby the drive shaft 29 is guided separately through the container bottom 3. Through the shearing head and the counter-shearing head, the mixed good that is dropping as described above is additionally mixed again along the shaft 8 via the rotating speed differences, rotating directions, gap widths and diameters of the shearing heads that are predominant here. In this area, the liquid can also be supplied very well, and it is mixed in an especially effective manner.

On the whole, the present invention shows an effective device for ensuring a mixed good preparation operating in the vertical direction, in which the maximum homogeneity requirements can be met while simultaneously keeping the batch times short. The different shearing effects over the zones of the mixer are especially advantageous in the process when liquids are added as mixing components, since in the area of the liquid additions, the increased shearing effect leads to a quick distribution of these components. Since this increased shearing effect only occurs locally, however, the drive output is, on the whole, not increased unnecessarily and the wear is also lowered. Also, fragile solid portions are not destroyed and are not exposed to any non-permitted high temperature increases.